

L3-SERIES PIPETTES



PIPETTES-L

Continuously adjustable pipette with tip ejector designed to measure and transfer liquids precisely and safely.

10 models in optimal volume ranges permit accurate measuring of any volume between 0,1 μ l to 10ml.

Characteristic Features:

- Perfect results of measurements
- Excellent ergonomical shape of the handle makes the work easy and pleasant
- Easy to read digital display
- Easy set up tip ejector's length for any kind of desired tip
- Easy removal of tip ejector when working with narrow tubes
- May be re-calibrated for solutions of any density and viscosity
- Each unit comes with an individual quality certificate, holder and re-calibration key
- Autoclavable shaft
- Maintenance free
- The pipette and its components are made of the best plastic and the best stainless steel and can be used safely with acid and alkaline solution

Cat. No.	Model	Volume Range μ l	Accuracy error %	Precision error %
3.1.1.	L2	0,1-2	12 - 1,5	6,0 - 0,7
3.1.2.	L10	0,5-10	4 - 0,5	4,0 - 0,4
3.1.3.	L20	2-20	4 - 0,8	3,0 - 0,4
3.1.3.0.	L50	5-50	3 - 0,8	3,0 - 0,4
3.1.4.	L100	10-100	1,6 - 0,8	0,3 - 0,3
3.1.5.	L200	20-200	1,2 - 0,6	0,6 - 0,3
3.1.5.0.	L250	50-250	1,2 - 0,6	0,6 - 0,3
3.1.6.	L1.000	100-1000	0,9 - 0,6	0,5 - 0,25
3.1.7.	L5.000	1000-5000	0,6 - 0,5	0,3 - 0,2
3.1.8.	L10.000	1000-10000	0,5 - 0,4	0,2 - 0,1